



LED front view



LED side/back view

SATURN 60AC - OGL LED dimmable down light 9.5 Watt, 850-950lm with built-in IC LED driver

The OGL Saturn 60 AC State-of-the-art design down light with inbuilt IC LED driver delivers high lumen output with exceptional quality of light and is one of the most advanced LED down light luminaires on the market.

- Features:**
- High lumen output to power consumption with no glare design
 - Dimmable with LED Wall AC Phase cut dimmer
 - Inbuilt IC LED driver with ultra-low inrush current
 - Power Factor >0.95
 - Over temperature protection
 - Very low ripple current enable California Title 24 flicker compliance
 - Super low profile luminaire
 - Approved for installation under ceiling insulation

Benefits:

- ✓ Designed and manufactured in Australia from highest quality components to achieve LED high performance and longevity of its operation
- ✓ Designed specifically for High Energy Rating Houses - Meets IP44 ingress protection standard and provides a superior seal to ceiling plaster boards with minimal infiltration from room to roof space
- ✓ Super slim - LED downlight can be fully covered by roof insulation lying flat across the top of the ceiling
- ✓ Easy installation with two spring clips
- ✓ No UV or IR emission
- ✓ Fully recyclable, RoHS compliant

Product description	Part Number	LED Power	Colour Temp	Lumens output	Beam Angle	CRI	Dimmable	Mechanical Data Frame finish	Luminaire Power	Operating temp	LED Globe IP rating	Efficacy	Rated Life	Compliance
SATURN 60 AC - OGL LED down light 10 Watt with integrated LED driver 240V AC 42mA	LH110-W09-W	8.5 Watt	3,000K	850lm	60deg	>80	YES	Diameter: 110mm Height: 25mm with brackets: 30mm White frame Cut out: 90-95mm	10 Watt	-20/+50deg C	IP44	100lm/W	30,000hrs	CE, C-tick
	LH110-N09-W	8.5 Watt	4,000K	900lm	60deg	>80	YES		10 Watt	-20/+50deg C	IP44	106lm/W	30,000hrs	CE, C-tick
	LH110-C09-W	8.5 Watt	6,500K	950lm	60deg	>80	YES		10 Watt	-20/+50deg C	IP44	118lm/W	30,000hrs	CE, C-tick

