



OGL LED Panel  
600x600mm



OGL LED Panel  
300x300mm

## OGL LED Flat Panel - Square

OGL LED Flat Panels are the most stylish, advanced and efficient products for interior and office general lighting.

High lumen output, high efficiency and reliability puts the OGL LED Flat Panel product ahead of any current fluorescent luminaires.

OGL LED Flat Panel with its low power consumption, no maintenance over the rated life time and with full recyclability makes this product truly environmental friendly.

**Available in three different mounting versions:**

1. Surface mount
2. Flush mount to suspended or plaster ceiling
3. Pendant drop up to 1.5 meters (longer drop on request)

### Benefits

- ✓ low ownership cost
- ✓ simple recycle process – contains no harmful substances, main component -acrylic panel - can be reused
- ✓ long life – design rated for 50 000 hours
- ✓ no maintenance required over the life of the luminaires
- ✓ full light output on start up – best product to be used in conjunction with occupancy sensor and daylight sensor
- ✓ no UV and IR emissions, generates less heat, reducing HVAC costs
- ✓ stable CRI and colour temperature over LED life time

Product description	Part Number	LED Power	Colour Temp	Lumens output	Beam Angle	CRI	Dimmable	Mechanical Data	Operating temp	IP rating	LED Efficacy	Rated Life	Compliance
OGL LED Flat Panel 300x300mm 14Watt	P-3030-W14	12 Watt	3,000K	1,016 lm	140deg	>80	Option	300 x 300 x 12 mm	-20/+50deg C	IP20	85 lm/W	50,000hrs	CE, C-tick
	P-3030-N14	12 Watt	4,000K	1,116 lm	140deg	>80	Option		-20/+50deg C	IP20	93 lm/W	50,000hrs	CE, C-tick
	P-3030-C14	12 Watt	5,500K	1,138 lm	140deg	>80	Option		-20/+50deg C	IP20	95 lm/W	50,000hrs	CE, C-tick
OGL LED Flat Panel 300x300mm 24Watt	P-3030-W24	21 Watt	3,000K	1,777 lm	140deg	>80	Option		-20/+50deg C	IP20	85 lm/W	50,000hrs	CE, C-tick
	P-3030-N24	21 Watt	4,000K	1,953 lm	140deg	>80	Option		-20/+50deg C	IP20	93 lm/W	50,000hrs	CE, C-tick
	P-3030-C24	21 Watt	5,500K	1,992 lm	140deg	>80	Option		-20/+50deg C	IP20	95 lm/W	50,000hrs	CE, C-tick
OGL LED Flat Panel 600x600mm 30Watt	P-6060-W30	27 Watt	3,000K	2,285 lm	140deg	>80	Option	600 x 600 x 12 mm	-20/+50deg C	IP20	85 lm/W	50,000hrs	CE, C-tick
	P-6060-N30	27 Watt	4,000K	2,511 lm	140deg	>80	Option		-20/+50deg C	IP20	93 lm/W	50,000hrs	CE, C-tick
	P-6060-C30	27 Watt	5,500K	2,561 lm	140deg	>80	Option		-20/+50deg C	IP20	95 lm/W	50,000hrs	CE, C-tick
OGL LED Flat Panel 600x600mm 36Watt	P-6060-W36	32 Watt	3,000K	2,708 lm	140deg	>80	Option		-20/+50deg C	IP20	85 lm/W	50,000hrs	CE, C-tick
	P-6060-N36	32 Watt	4,000K	2,976 lm	140deg	>80	Option		-20/+50deg C	IP20	93 lm/W	50,000hrs	CE, C-tick
	P-6060-C36	32 Watt	5,500K	3,036 lm	140deg	>80	Option		-20/+50deg C	IP20	95 lm/W	50,000hrs	CE, C-tick
OGL LED Flat Panel 600x600mm 48Watt	P-6060-W48	42 Watt	3,000K	3,554 lm	140deg	>80	Option		-20/+50deg C	IP20	85 lm/W	50,000hrs	CE, C-tick
	P-6060-N48	42 Watt	4,000K	3,906 lm	140deg	>80	Option		-20/+50deg C	IP20	93 lm/W	50,000hrs	CE, C-tick
	P-6060-C48	42 Watt	5,500K	3,984 lm	140deg	>80	Option		-20/+50deg C	IP20	95 lm/W	50,000hrs	CE, C-tick